

MAX-SERIES

RT-65

**MORE RELIABLE.
MORE DURABLE.
MORE ABLE.**



Introducing the brand-new RT-65 MAX-Series Posi-Track® compact track loader. This premium mid-size loader features maximum power, comfort and serviceability—which leads to more productivity. The RT-65 offers ASV's patented Posi-Track technology, best-in-class ground clearance and unmatched performance for digging and ground engagement work. And with the MAX-Series cab features—like premium 360-degree visibility, a state-of-the-art control panel and more room than ever—operators will be able to work like never before. Experience the ASV Posi-Track difference and rely on the incredible abilities of the RT-65.

// OUTSTANDING RELIABILITY. PREMIUM POWER. EXCELLENT SERVICEABILITY.

asv

RT-65 COMPACT TRACK LOADER

OPERATING SPECIFICATIONS

LOADER ARMS	Radial
OPERATING WEIGHT	7,480 lbs (3393 kg)
SHIPPING WEIGHT	6,759 lbs (3066 kg)
GROUND PRESSURE AT OPERATING WEIGHT	4.2 psi (29.0 kPa)
RATED OPERATING CAPACITY (35% of tipping load)	1,925 lbs (873 kg)
OPERATING CAPACITY (50% of tipping load)	2,750 lbs (1247 kg)
TIPPING LOAD	5,500 lbs (2495 kg)
TRAVEL SPEED, MAXIMUM	10.6 mph (17.1 kph)

ENGINE

TYPE	Diesel, 3-cylinder, aftercooled, turbo charged
MODEL	Deutz TCD2.2 T4F
DISPLACEMENT	134.3 in. (2.2 L)
GROSS POWER RATING AT 2800 RPM	67 hp (50 kW)
TORQUE, PEAK	184.4 ft-lb (250 Nm)
COOLING SYSTEM	Temperature-controlled variable speed hydraulically-driven fan and coolant/anti-freeze-filled radiator
INTAKE AIR CLEANER	Dual stage
EMISSION CONTROLS	Meets all U.S. EPA Tier 4 final standards

UNDERCARRIAGE

TRACK TYPE: General purpose track constructed of rubber compound with embedded co-polymer cords and all-purpose treads.

TRACK WIDTH	15 in. (381 mm)
LENGTH OF TRACK ON GROUND	59 in. (1499 mm)
GROUND CONTACT AREA	1,770 in. ² (1.14 m ²)
DRIVE SYSTEM	2 hydrostatic direct drive sprockets controlled by single joystick
TRACK DRIVE SPROCKET	Elevated with low friction, replaceable sprocket rollers
UNDERCARRIAGE SUSPENSION	2 independent torsion axles per undercarriage
ROLLER WHEELS	24 high-density polyurethane and rubberwheels per track. Wheels include sealed bearings
ROLLER WHEEL DIAMETER	Front & rear wheels: 14 in. (355.6 mm) Middle wheels: 10 in. (254 mm)

AUXILIARY HYDRAULIC SYSTEM

STANDARD PUMP CAPACITY	0-22.2 gpm (84 lpm)
OPTIONAL HIGH FLOW	27.4 gpm (103.7 lpm)
SYSTEM PRESSURE, MAX.	3300 psi (22753 kPa)
CONTROLS	Variable flow via joystick rocker switch or continuous via dash-mounted switch
COUPLERS	Push-to-connect quick couplers mounted on loader arms. Pressure relief valve mounted to coupler block
COOLING SYSTEM	High efficiency oil cooler beside engine radiator, not stacked

ELECTRICAL SYSTEM

NOMINAL CHARGE	12 V
BATTERY	800 CCA
CHARGING SYSTEM	120 amp alternator
OUTLETS	1-12 V port inside operator station
WIRING	Pre-wired for all factory-available accessories

OPERATOR STATION

SEAT: Vinyl seat with built in operator presence switch, Operator Manual pouch, and 2 in (51 mm) wide seat belt, adjustable position seat optional

LOADER CONTROL: Right-hand pilot hydraulic joystick controls loader lift, lower and tilt, plus intermittent control of auxiliary hydraulic.

DRIVE CONTROL: Left-hand pilot hydraulic joystick controls machine speed and direction.

ENGINE SPEED Hand-operated dial, foot throttle optional.

MACHINE DISPLAY: Engine RPM, engine oil pressure, hydraulic oil high temperature, engine coolant temperature, battery voltage, hourmeter, fuel level, trip meter, engine diagnostics, system monitoring, fault logging. Deluxe includes: 7" color touch screen, integrated rear view camera, password protection with user profiles, job clock, maintenance schedules

ROPS	Restraint-ISO 6683, SAE J2292, Cal OSHA 1596,ISO 3471
FOPS	Meets ISO 3449: Level I and II (Optional)
ILLUMINATION	2 - Fixed forward-facing halogen lights 2 - Adjustable rear-facing halogen light 2 - LED Side lights (optional) 1 - Interior light
CONVENIENCE	12 V Power Port, Easy access diagnostic ports, Easy access fuse panels, Emergency seat belt cutter/glass breaker
STANDARD FEATURES	Horn, backup alarm, cupholder, phoneholder, behind seat storage, rear view mirror, lapbar, roof escape hatch, roof panel & rear cab windows. Premium Features: Adjustable joystick & arm rest positions, adjustable directional & air flow HVAC vents, radio with bluetooth & USB, frameless front door, attachment control kit, wiper/washer, beacon switch/outlet, easy-off door

